

Zuma Lighting shall not be responsible for any damage that occurs during or after installation, or for any structure that has been modified by the purchaser or is used in some way other than our application recommendations.

- The purchaser and installer must provide electrical groundings and warnings about electrical hazards in accordance with applicable codes.

1. Attach sling to top of pole.
2. Attach luminaries and complete wiring.
3. Place leveling nuts and washers on anchor bolts.
4. Erect pole.
5. Position over anchor bolts and set on leveling nut washers.
6. Place anchor nuts and washers on anchor bolts and tighten once pole is plumb.

- Our quotations will reflect a suggested burial depth.
- Soil and site locations will vary, for this reason, it is imperative to consult with a qualified engineer with knowledge of the local soil conditions.
- Zuma Lighting cannot be responsible for decisions made regarding the installation, embedded depth or factors related to the specific site location.

- The concrete foundation must be designed by a qualified engineer with knowledge of the local soil conditions.
- Anchor bolt diameter, length and psi are specifically selected to withstand load limitations listed in the catalog or quote.
- Anchorage supplied by others:
  - » Contact the factory for the correct size and strength.
  - » Zuma Lighting will not be held responsible for the structural integrity of the system if anchor bolts are supplied by others.
- The bolt circle template provided conforms to the bolt circle of the pole base.
- When leveling nuts are used, the bottom of the lowest leveling nut shall not be more than 1" from the concrete surface.
  - » Large spaces between the pole base plate and the concrete can cause excessive stresses in the anchor bolts.

